## PF-2905/NEC/US (USSN 09/986,412)

## LISTING OF THE CLAIMS

What is claimed is:

1	1. (Currently amended) A method of updating a program in a terminal device
2	such that update data and an existent program may be stored separately within
3	said terminal device, wherein
4	if a transmission of update data from a base station to a terminal device is
5	interrupted due to any disconnection between them, then after it is verified that the
6	terminal device becomes connected to the base station, said transmission process is
7	re-started for remaining parts of the update data;
8	said update data are divided into a plurality of data sets by said base station
9	and said plural data sets are added with sequential pointers respectively; and
10	an arithmetic unit verifies a pointer of a completely received final update data
11	set and determines a next pointer in connection with the next data set which should be
12	received next.
1	2. (Canceled)
1	3. (Currently amended) The method as claimed in claim 1 2, wherein after one with
2	next pointer for said remaining data set is confirmed, then the data set with the next
3	pointer is first transmitted during said re-transmission processes
1	4. (Original) The method as claimed in claim 1, wherein after all of said update data
2	are transmitted, then an operation test is automatically started.
1	5. (Original) The method as claimed in claim 3, wherein after all of said update data
2	are transmitted, then an operation test is automatically started.

## PF-2905/NEC/US (USSN 09/986,412)

1

6. (Currently amended) A terminal device including:

2	a receiving unit for receiving update data transmitted;
3	an updating unit for receiving said update data and updating an existent
4	program with said update data, such that said update data and existent program may
5	be stored separately within the terminal device them; and
6	an additional unit for transmitting said remaining data sets with reference to
7	pointers added to said data sets;
8	an arithmetic unit for verifying a pointer of a completely received final update
9	data set and determining a next pointer in connection with the next data set which
10	should be received next; and
11	a re-starting unit for re-starting transmission process of remaining
12	non-transmitted parts of the update data, after it is verified that the terminal device
13	becomes connected to the base station, if a transmission of update data from a base
14	station to a terminal device is interrupted due to any disconnection between.
1	7. (Canceled)
1	8. (Original) The device as claimed in claim 6, wherein after all of said update data
2	are transmitted, then an operation test is automatically started.
1	9. (Original) The device as claimed in claim 8, further including a re-writing unit for
2	re-writing said updated program into said program existent in said mobile terminal.